



MOTOTRBO™

DGR™ 6175 Repeater



Shift into Digital.

The next-generation professional two-way radio communications solution is here, with more performance, productivity and value—thanks to digital technology that delivers increased capacity and spectrum efficiency, integrated data communications and enhanced voice communications.

MOTOTRBO offers you a private, standards-based, cost-effective solution that can be tailored to meet your unique coverage and feature needs.

This versatile portfolio provides a complete system of portable radios, mobile radios, repeaters, accessories and data applications—a complete solution.

Key Features

Supports two simultaneous voice or data paths in digital Time-Division Multiple-Access (TDMA) mode.

Doubles the number of users you can have on a single licensed 12.5 kHz channel.

Integrates voice and data to increase operational efficiency.

100% continuous full duty cycle up to 45W VHF and 40W UHF.

Integrated power supply.

LEDs clearly indicate transmit and receive modes in both channel slots as well as operation in digital or analog modes.

Rack-mount is standard; wall-mount kit also available.

Sturdy handles make installation and handling easier.

Automated battery back-up available (battery sold separately).

Supports applications including MOTOTRBO Text Messaging Services and MOTOTRBO Location Services (GPS location tracking).

MOTOTRBO is a complete two-way radio system that includes portable and mobile radios, repeaters, accessories and applications.

MOTOTRBO DGR 6175 REPEATER SPECIFICATIONS

GENERAL	VHF	UHF	
		BAND I	BAND II
Channel Capacity		1	
Typical RF Output	1-25 W	1-25 W	1-40 W
	25-45 W	25-40 W	(1-25 W above 512 MHz)
Frequency	136-174 MHz	403-470 MHz	450-527 MHz
Dimensions (HxWxL)	5.22 x 19 x 11.67 in		
	(132.6 x 482.6 x 296.5 mm)		
Weight	31 lbs. (14 kg)		
Current Drain: Standby	1 A (1 A DC typical)		
	Transmit	3.8 A (11 A DC typical)	
Operating Temperature Range	-30°C to +60°C		
Max Duty Cycle	100%		
FCC Description	ABZ99FT3026		ABZ99FT4026
	ABZ99FT3025		ABZ99FT4025

RECEIVER	VHF	UHF	
		BAND I	BAND II
Frequencies	136-174 MHz	403-470 MHz	450-527 MHz
Channel Spacing	12.5 kHz / 25 kHz		
Frequency Stability	+/- 0.5 ppm		
(-30° C, +60° C, +25° C)			
Analog Sensitivity (12dB SINAD)	0.3 uV		
	0.22 uV (typical)		
Digital Sensitivity	5% BER: 0.3 uV		
Intermodulation (TIA603C)	78 dB		75 dB
Adjacent Channel Selectivity	65 dB @ 12.5 kHz, 75 dB @ 25 kHz		
	50 dB @ 12.5 kHz, 75 dB @ 25 kHz		
Spurious Rejection (TIA603C)	80 dB		75 dB
Audio Distortion @ Rated Audio	3% (typical)		
Hum and Noise	-40 dB @ 12.5 kHz		
	-45 dB @ 25 kHz		
Audio Response	TIA603C		
Conducted Spurious Emission	-57 dBm		

TRANSMITTER	VHF	UHF	
		BAND I	BAND II
Frequencies	136 - 174 MHz	403-470 MHz	450-527 MHz
Channel Spacing	12.5 kHz / 25 kHz		
Frequency Stability	+/- 0.5 ppm		
(-30° C, +60° C, +25° C)			
Power Output	1-25 W	1-25 W	1-40 W
	25-45 W	25-40 W	(1-25 W above 512 MHz)
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz		
	+/- 5.0 kHz @ 25 kHz		
FM Hum and Noise	-40 dB @ 12.5 kHz		
	-45 dB @ 25 kHz		
Conducted / Radiated Emission	-36 dBm < 1 GHz		
	-30 dBm > 1 GHz		
Adjacent Channel Power (TIA603C)	60 dB @ 12.5 kHz		
	70 dB @ 25 kHz		
Audio Response	TIA603C		
Audio Distortion	3%		
FM Modulation	12.5 kHz: 11K0F3E		
	25 kHz: 16K0FE		
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD		
	12.5 kHz Data & Voice: 7K60FXE		
Digital Vocoder Type	AMBE++		
Digital Protocol	ETSI-TS102 361-1		

Quality / Reliability



Backed by a two-year Standard Warranty

MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © 2008 Motorola, Inc. All rights reserved. LE-MTRBO-6175-PS-8-08

Specifications subject to change without notice. All specifications shown are typical.


 Recommended Dealer:
www.hkrsolutions.com
HKRSolutions
 Two-way Radio & Accessories Specialist