



THE FUTURE OF BUSINESS COMMUNICATION, DELIVERED TODAY

# MOTOTRBO™ DIGITAL TWO-WAY MOBILE RADIOS

Make technology more productive and personal. You asked for a forward-thinking way to connect your people to their work, wherever they go. An innovative business tool that increases their efficiency while lowering your costs. Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. It integrates voice and data seamlessly, offers enhanced features that are easy to use and delivers increased capacity to meet your communication needs from the field to the factory floor. With exceptional voice quality and long battery life, MOTOTRBO keeps your work teams connected when communication is a must.

## HIGH-POWERED PERFORMANCE

Because MOTOTRBO uses TDMA digital technology, it delivers integrated voice and data, twice the calling capacity plus clearer voice communications. In fact, the leading-edge IMPRES™ technology in our audio accessories also ensures clearer audio delivery.

## INDUSTRY-LEADING APPLICATIONS

Motorola's Application Developer Program offers customized data applications so you can adapt your radios to your unique business needs. Because we've created the largest developer program in the industry, we can provide nimble applications that address your challenges and answer your objectives – from work order ticket management to network management, email gateways to location tracking, dispatch consoles to telephony integration, and beyond.

Whether you want to send text messages or track work order information, pinpoint work crew locations with integrated GPS or manage your fleet from a central dispatch location, MOTOTRBO paves the way – with customizable data applications on one convenient device.

**ADDED FUNCTIONALITY**

MOTOTRBO offers added functionality, including dispatch capability with the MIP 5000 VoIP console, enhanced call signaling, basic and enhanced privacy-scrambling, option board expandability and compatibility with SCADA solutions for utility and public service monitoring and alarms. Plus digital telephone interconnect capability to enable communication between radios and landline or mobile phones as well as a transmit interrupt suite – with voice interrupt, emergency voice interrupt or data over voice interrupt – to prioritize critical communication the moment you need it.

**EXPANDED CAPACITY AND COVERAGE**

Your workforce is hard at work every day – picking up loads, making road repairs, providing security, responding to guest requests or restoring power after a storm. That’s why you need the proven performance of MOTOTRBO radio systems for non-stop communication no matter the size of your work force, no matter where they go.

MOTOTRBO’s IP Site Connect dramatically improves customer service and productivity by using the Internet to extend coverage to users anywhere in the world. Our scalable, single-site Capacity Plus solution expands capacity

to over 1,000 users without adding new frequencies. Connect Plus multi-site digital trunking enables you to accommodate the high volume, wide area communication your business requires. Whether you need coverage at a single site or across multiple sites, MOTOTRBO can be scaled to meet your needs.

**MIGRATE AT YOUR OWN PACE**

Keeping operations running smoothly during a change in communication systems is vital to your business. It’s easy to migrate to digital with MOTOTRBO because radios operate in analog and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analog and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analog system, and when your time and budget allow you can begin migrating to digital at your own pace.

**RELIABLE DURABILITY**

MOTOTRBO mobile radios are backed by a two-year Standard Warranty, one-year Repair Service Advantage (US)/Extended Warranty (Canada) and minimum 1-year warranty for accessories.



**XPR™ 4550 / XPR 4580**  
Display Mobile Radios

**XPR 4350 / XPR 4380**  
Numeric Display Mobile Radios

MOTOTRBO™ XPR™ 4550/XPR 4350 MOBILE RADIOS

**GENERAL SPECIFICATIONS**

	DISPLAY XPR 4550			NUMERIC DISPLAY XPR 4350		
	VHF	UHF Band I	UHF Band II	VHF	UHF Band I	UHF Band II
Channel Capacity	Up to 1,000			32		
Typical RF Output						
Low Power	1-25 W	1-25 W	—	1-25 W	1-25 W	—
High Power	25-45 W	25-40 W	1-40 W	25-45 W	25-40 W	1-40 W
Frequency	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz
Dimensions	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)			2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)		
Weight	4.0 lbs (1.8 kg)			4.0 lbs (1.8 kg)		
Current Drain:						
Standby	0.81 A max	0.81 A max	0.81 A max	0.81 A max	0.81 A max	0.81 A max
Rx @ Rated Audio	2 A max	2 A max	2 A max	2 A max	2 A max	2 A max
Transmit	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max	1-40 W: 14.5 A max (11.0 A max < 25 W)	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max	1-40 W: 14.5 A max (11.0 A max < 25 W)
FCC Description	1-25 W: ABZ99FT3083 25-45 W: ABZ99FT3082	1-25 W: ABZ99FT4081 25-40 W: ABZ99FT4080	1-40 W: ABZ99FT4083	1-25 W: ABZ99FT3083 25-45 W: ABZ99FT3082	1-25 W: ABZ99FT4081 25-40 W: ABZ99FT4080	1-40 W: ABZ99FT4083
IC Description	1-25 W: 109AB-99FT3083 25-45 W: 109AB-99FT3082	1-25 W: 109AB-99FT4081 25-40 W: 109AB-99FT4080	1-40 W: 109AB-99FT40830	1-25 W: 109AB-99FT3083 25-45 W: 109AB-99FT3082	1-25 W: 109AB-99FT4081 25-40 W: 109AB-99FT4080	1-40 W: 109AB-99FT4083

**RECEIVER: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350**

**GPS: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350**

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)		
Channel Spacing	12.5 kHz / 25 kHz*			TTF (Time To First Fix) Cold Start	< 1 minute	
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm			TTF (Time To First Fix) Hot Start	< 10 seconds	
Analog Sensitivity (12dB SINAD)	0.3 uV 0.22 uV (typical)			Horizontal Accuracy	< 10 meters	
Digital Sensitivity	5% BER: 0.3 uV			<b>MILITARY STANDARDS: DISPLAY XPR 4550 &amp; NUMERIC DISPLAY XPR 4350</b>		
Intermodulation (TIA603C)	78 dB	75 dB		<b>810E</b>		<b>810F</b>
Adjacent Channel Selectivity				Applicable MIL-STD	Methods	Procedures
TIA603	65 dB @ 12.5 kHz, 80 dB @ 25 kHz*	65 dB @ 12.5 kHz, 75 dB @ 25 kHz*		Low Pressure	500.3	II
TIA603C	50 dB @ 12.5 kHz, 80 dB @ 25 kHz*	50 dB @ 12.5 kHz, 75 dB @ 25 kHz*		High Temperature	501.3	I/A, II/A1
Spurious Rejection (TIA603C)	80 dB	75 dB		Low Temperature	502.3	I/C3, II/C1
Rated Audio	3 W (Internal)			Temperature Shock	503.3	I/A1C3
	7.5 W (External - 8 ohms)			Solar Radiation	505.3	I
	13 W (External - 4 ohms)			Rain	506.3	I, II
Audio Distortion @ Rated Audio	3% (typical)			Humidity	507.3	II
Hum and Noise	-40 dB @ 12.5 kHz			Salt Fog	509.3	I
	-45 dB @ 25 kHz*			Dust	510.3	I
Audio Response	TIA603C			Vibration	514.4	I/10, II/3
Conducted Spurious Emission (TIA603C)	-57 dBm			Shock	516.4	I, IV

**TRANSMITTER: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350**

**ENVIRONMENTAL SPECIFICATIONS: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350**

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Operating Temperature	-30° C / +60° C
Channel Spacing	12.5 kHz / 25 kHz*			Storage Temperature	-40° C / +85° C
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm			Thermal Shock	Per MIL-STD
Low Power Output	1-25 W	1-25 W	—	Humidity	Per MIL-STD
High Power Output	25-45 W	25-40 W	1-40 W	ESD	IEC-801-2KV
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz*			Dust and Water Intrusion	IEC 60529 - IP54
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz*			Packaging Test	MIL-STD 810D and E
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz				
Adjacent Channel Power	60 dB @ 12.5 kHz 70 dB @ 25 kHz*				
Audio Response	TIA603C				
Audio Distortion	3%				
FM Modulation	12.5 kHz: 11K0F3E 25 kHz*: 16K0F3E				
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE				
Digital Vocoder Type	AMBE +2™				
Digital Protocol	ETSI TS 102 361-1, -2, -3				

\*25 kHz will not be available on new equipment in the U.S. after 1/1/2013.  
Specifications subject to change without notice. All specifications shown are typical.  
Radio meets applicable regulatory requirements. Version 9 03/10

**GENERAL SPECIFICATIONS**

	DISPLAY XPR 4580	NUMERIC DISPLAY XPR 4380	GPS																																					
Channel Capacity	Up to 1,000	Up to 32	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)																																					
Typical RF Output	806-870 MHz 10-35 W 896-941 MHz* 10-30 W	806-870 MHz 10-35 W 896-941 MHz* 10-30 W	TTFF (Time To First Fix) Cold Start	< 1 minute																																				
Frequency Band	800 and 900 MHz	800 and 900 MHz	TTFF (Time To First Fix) Hot Start	< 10 seconds																																				
Dimensions	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)	Horizontal Accuracy	< 10 meters																																				
Weight	4.0 lbs (1.8 kg)	4.0 lbs (1.8 kg)	<b>MILITARY STANDARDS</b>																																					
Current Drain:																																								
Standby	0.81 A max	0.81 A max	Applicable MIL-STD	<table border="1"> <thead> <tr> <th colspan="2">810E</th> <th colspan="2">810F</th> </tr> <tr> <th>Methods</th> <th>Procedures</th> <th>Methods</th> <th>Procedures</th> </tr> </thead> <tbody> <tr> <td>Low Pressure</td> <td>500.3</td> <td>II</td> <td>500.4</td> </tr> <tr> <td>High Temperature</td> <td>501.3</td> <td>I/A, II/A1</td> <td>501.4</td> </tr> <tr> <td>Low Temperature</td> <td>502.3</td> <td>I/C3, II/C1</td> <td>502.4</td> </tr> <tr> <td>Temperature Shock</td> <td>503.3</td> <td>I/A1C3</td> <td>503.4</td> </tr> <tr> <td>Solar Radiation</td> <td>505.3</td> <td>I</td> <td>505.4</td> </tr> <tr> <td>Rain</td> <td>506.3</td> <td>I, II</td> <td>506.4</td> </tr> <tr> <td>Humidity</td> <td>507.3</td> <td>II</td> <td>507.4</td> </tr> </tbody> </table>	810E		810F		Methods	Procedures	Methods	Procedures	Low Pressure	500.3	II	500.4	High Temperature	501.3	I/A, II/A1	501.4	Low Temperature	502.3	I/C3, II/C1	502.4	Temperature Shock	503.3	I/A1C3	503.4	Solar Radiation	505.3	I	505.4	Rain	506.3	I, II	506.4	Humidity	507.3	II	507.4
810E		810F																																						
Methods	Procedures	Methods	Procedures																																					
Low Pressure	500.3	II	500.4																																					
High Temperature	501.3	I/A, II/A1	501.4																																					
Low Temperature	502.3	I/C3, II/C1	502.4																																					
Temperature Shock	503.3	I/A1C3	503.4																																					
Solar Radiation	505.3	I	505.4																																					
Rain	506.3	I, II	506.4																																					
Humidity	507.3	II	507.4																																					
Rx @ Rated Audio	2 A max	2 A max																																						
Transmit	12.0 A max	12.0 A max																																						
Power Supply	12 V dc Negative Ground	12 V dc Negative Ground																																						
FCC Description	ABZ99FT5010	ABZ99FT5010																																						
IC Description	109AB-99FT5010	109AB-99FT5010																																						
<b>RECEIVER</b>			<b>ENVIRONMENTAL SPECIFICATIONS</b>																																					
Frequencies	800 MHz: 854-866 MHz and 869-870 MHz 900 MHz: 935-941 MHz		Operating Temperature	-30° C / +60° C																																				
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz		Storage Temperature	-40° C / +85° C																																				
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm		Thermal Shock	Per MIL-STD																																				
Analog Sensitivity (12dB SINAD)	0.22 uV		Humidity	Per MIL-STD																																				
Digital Sensitivity	5% BER: 0.28 uV		ESD	IEC-801-2KV																																				
Intermodulation (TIA603C)	78 dB		Dust and Water Intrusion	IEC 60529 - IP54																																				
Adjacent Channel Selectivity TIA603 TIA603C	65 dB @ 12.5 kHz, 75 dB @ 25 kHz 50 dB @ 12.5 kHz, 75 dB @ 25 kHz		Packaging Test	MIL-STD 810D and E																																				
Spurious Rejection (TIA603C)	75 dB		<b>ONLY THE FOLLOWING FREQUENCIES ARE SUPPORTED BY THE XPR 4580 / XPR 4380</b>																																					
Rated Audio	3 W (Internal)		<b>Band</b>	<b>Receive</b>																																				
Audio Distortion @ Rated Audio	3% (typical)			<b>Transmit</b>																																				
Hum and Noise	-45 dB @ 12.5 kHz / -45 dB @ 25 kHz		800 MHz																																					
Audio Response	TIA603C																																							
Conducted Spurious Emission (TIA603C)	-57 dBm																																							
<b>TRANSMITTER</b>																																								
Frequencies	800 MHz: 809-821 MHz, 824-825 MHz, 854-866 MHz and 869-870 MHz 900 MHz: 896-902 MHz and 935-941 MHz																																							
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz																																							
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm																																							
Low Power Output	10 W																																							
High Power Output	800 MHz: 35W / 900 MHz: 30W																																							
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz / +/- 5.0 kHz @ 25 kHz																																							
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz																																							
Conducted / Radiated Emission	-36 dBm < 1 GHz / -30 dBm > 1 GHz																																							
Adjacent Channel Power	-50 dB @ 12.5 kHz / -60 dB @ 25 kHz																																							
Audio Response	TIA603C																																							
Audio Distortion	3%																																							
FM Modulation	12.5 kHz: 11K0F3E / 25 kHz: 16K0F3E																																							
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE																																							
Digital Vocoder Type	AMBE +2™		900 MHz																																					
Digital Protocol	ETSI TS 102 361-1, -2, -3																																							

\*For frequencies 901-902, 940-941 MHz, FCC Rule Part 24 limits power to 7W ERP. Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements. Version 1 03/10

For more information on how to make your business more efficient and better connected, visit.

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196  
U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2011 Motorola Solutions, Inc. All rights reserved. R3-1-2038B

